

Manufacturer
Outdoor unit
Indoor unit
Indoor unit



2MXM40A2V1B9

FTXP20N5V1B9

FTXP20N5V1B9

Outdoor sound power level (dB)	dB(A)
Indoor sound level	dB(A)
The refrigerant (GWP)	

55.0

R-32 (675)

Cooling mode

SEER	
Energy efficiency class	
Annual electricity consumption	kWh/a
Design load Pdesignc	kW

7.73

A++

181.0

4.0

Heating mode: Average climate
Design temperature = -10°C

SCOP	
Energy efficiency class	
Annual electricity consumption	kWh/a
Design load Pdesignh at -10°C	kW
Required back up heating capacity at -10°C	kW
Declared capacity at -10°C	kW

4.3

A+

1041.0

3.2

3.2

Heating mode: Warm climate
Design temperature = 2°C

SCOP	
Energy efficiency class	
Annual electricity consumption	kWh/a
Design load Pdesignh at 2°C	kW
Required back up heating capacity at 2°C	kW
Declared capacity at 2°C	kW

Heating mode: Cold climate
Design temperature = -22°C

SCOP	
Energy efficiency class	
Annual electricity consumption	kWh/a
Design load Pdesignh at -22°C	kW
Required backup heating capacity at -22°C	kW
Declared capacity at -22°C	kW

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.