

## UN 38.3 Test Summary Report

Lithium Cell or Rattery Test Summary in Accordance with Section 2.9.4 LIN Model Regulations and Sub-section 38.3 of the LIN Manual of Tests and Criteria, Part III, subsection 38.3.5

☑ Tested Type Part #: TLP-91821/A

☑ Same Type Part #: and TLP-91321/A

[b] Manufacturer

Tadiran Batteries Ltd.

P.O. Box 1 Kiryat Ekron

Israel 70500

T. +972 8 9 44 560

sales@tadiran-batt.com

www.tadiran.com

[d] Unique report ID: 15Q-834

[e] Report date: 2008.12.01

[c] Test Laboratory

Tadiran Batteries Ltd.

P.O. Box 1 Kiryat Ekron

Israel 70500 T. +972 8 9 44 560

sales@tadiran-batt.com

www.tadiran.com

Same Type Part Numbers # (all): All configurations with harness and cable of this battery with
 part number 17 9 18211 xx. The Type can either be TLP- or SLP-.

[f] (i) $\square$ Li-ion $\boxtimes$ Li-metai.
--

(iv) <u>Description:</u> Primary (non-rechargeable) 3.7 V Lithium Thionyl Chloride (Li-SOCI2) hybrid battery, assembled from 2 (two) "AA" sized SL-860 cells and 1 (one) "AAA/2" sized HLC-1020. The TLP-91821/A battery may come with optional suffixes consisting of a "/" followed by one or more letters and a digit. These suffixes indicate different types of finishing to the battery e.g. harness. The battery may also start with the letters SLP-. Tadiran manufactures all cells/batteries under a quality management system as required under this regulation.

(ii) Mass: 28 g

(iii) ⊠ Watt hour rating or ⊠ Lithium content: 0.07 Wh and 1.3 g

(v) □ Cell ⊠ Battery □ Product. Model number/Part number: TLP-91821/A

[g] List of Tests Conducted	Result (Pass / Fail / N.A.)	Test record reference	
38.3.4.1 T.1: Altitude simulation	Pass	Summery page 2	
38.3.4.2 T.2: Thermal test	Pass	Summery page 2	
38.3.4.3 T.3: Vibration	Pass	Summery page 2	
38.3.4.4 T.4: Shock	Pass	Summery page 2	
38.3.4.5 T.5: External short circuit	Pass	Summery page 2	
38.3.4.6 T.6: Impact/Crush (cell only test)	Pass	Summery page 2	
38.3.4.7 T.7: Overcharge (N.A for Li-metal only)	N.A.	N.A.	
38.3.4.8 T.8: Forced discharge (cell only test)	Pass	Summery page 2	
[h] Battery assembly: ☐ Not Applicable. ☒ UN38.3.3 (f) ☐ UN38.3.3 (g)			
[i] Test Reference: UN Manual of Tests and Criteria, Part III, sub-section 38.3. fifth revised edition			

[j] Signatory A. Date: 2018.12.12
Name: Marc Henn
Title: Application Engineering Manager

Signature.



[j] Signatory B. Date: 2018.12.12 Name: Olaf G. Lichtlein

Title: General Manager

Signature.

Important! The above signatory / signatories affirm that this document is a true and correct summary of the original individual tests and test data. The original test data is confidential information available to competent State Authorities with valid identification and only upon their formal request. Disclosure of the original test data to any other entity upon its request will be considered by Tadiran and, should Tadiran consider this request is with merit, may be subject to the prior execution of a nondisclosure agreement.